

**Amendments to the Claims:**

Following is a complete listing of claims, including current amendments, which listing reflects all claims currently in the application.

1. (Currently amended) ~~In a~~ A modified gravity-feed towel dispenser for dispensing C-fold and interfolded towels, wherein said dispenser houses C-fold or interfolded towels having a transverse length, L, which are positioned to be dispensed through an elongated bottom dispensing aperture having a length of L or greater, said towel dispenser including means for defining a top portion, a front wall, a back wall and a pair of side walls of said towel dispenser, as well as a bottom portion collectively defining an interior for receiving a stack of C-fold or interfolded towels ~~to be dispensed through said aperture~~, said bottom portion of said towel dispenser defining said elongated bottom dispensing aperture[;], wherein an adapter plate for securing is secured to said bottom portion of said towel dispenser and is configured to abridge the length of said dispensing aperture to a length L' of from about 80 percent to about 90 percent of said transverse length, L, of said C-fold or interfolded towels.
2. (Currently amended) The ~~adapter plate towel dispenser~~ according to Claim 1, wherein the adapter plate is an elongate member with a generally planar medial portion and further comprises a pair of terminal portions projecting outwardly and upwardly with respect to the planar medial portion at each end of said adapter plate, such that the terminal portions are upwardly inclined with respect to the medial portion of the plate.
3. (Currently amended) The ~~adapter plate towel dispenser~~ according to Claim 2, wherein said elongated dispensing aperture is abridged to a length, L', of about 85 percent of the transverse length L of said C-fold or interfolded towels.
4. (Currently amended) The ~~adapter plate towel dispenser~~ according to Claim 2, wherein the upwardly inclined terminal portions have an angle of inclination of from about 10 to about 30 degrees with respect to the generally planar medial portion of the adapter plate.

5. (Currently amended) The ~~adapter plate~~ towel dispenser according to Claim 4, wherein the upwardly inclined terminal portions have an angle of inclination of about 20 degrees with respect to the generally planar medial portion of the adapter plate.
6. (Currently amended) The ~~adapter plate~~ towel dispenser according to Claim 2, pivotally secured to the lower portion of said gravity-feed towel dispenser.
7. (Currently amended) The ~~adapter plate~~ towel dispenser according to Claim 1, wherein said adapter plate is configured to define a central enlarged portion of the dispensing aperture and two restricted terminal portions of the dispensing aperture each of the portions having a span perpendicular to the length of the dispensing aperture.
8. (Currently amended) The ~~adapter plate~~ towel dispenser according to Claim 7, wherein said enlarged central portion has a span of at least about twice the span of the restricted terminal portions.
9. (Currently amended) The ~~adapter plate~~ towel dispenser according to Claim 8, wherein the terminal portions of the dispensing aperture have a span of from about 20 to about 40 percent of the width of said interfolded towels corresponding thereto.
10. (Currently amended) The ~~adapter plate~~ towel dispenser according to Claim 9, wherein said restricted terminal portions of said aperture have a span of about 30 percent of the width of said interfolded towels corresponding thereto and a collective length of at least about 40 percent of the abridged length L' of said dispensing aperture.

Claim 11-20 (Canceled)

21. (Currently amended) In a gravity-feed towel dispenser for dispensing C-fold and interfolded towels, wherein said dispenser contains C-fold or interfolded towels having a transverse length, L, which are positioned to be dispensed through an elongated bottom dispensing

aperture having a length of L or greater, said towel dispenser including means for defining a top portion, a front wall, a back wall and a pair of side walls of said towel dispenser, as well as a bottom portion collectively defining an interior for receiving a stack of C-fold or interfolded towels ~~to be dispensed through said aperture~~, said bottom portion of said towel dispenser defining said elongated bottom dispensing aperture, said dispenser being of the class that are moved forwardly for reloading; the improvement comprising an adapter plate secured to said bottom portion of said towel dispenser configured to abridge the length of said dispensing aperture to a length L' of from about 80 percent to about 90 percent of said transverse length, L, of said C-fold or interfolded towels, wherein the adapter plate is pivotally secured to the dispenser to accommodate reloading.

22. (Previously presented) The improvement according to Claim 21, wherein said adapter plate is pivotally secured to the sidewalls of the dispenser.